



GEM-DLS40

PULSED LASER DRIVER

The GEM-DLS40 has optimized the HV-DC source and trigger circuitry in size and functionality to fit in just 16 cm². Its typical application is driving pulsed laser diodes.



ELECTRICAL SPECIFICATIONS

- Output current: 8-40A (switchable with adjustable resistor)
- Max output voltage: 70V
- Rise time: ~ 5ns
- Trigger delay ~ 30ns
- Minimum pulse length: 15ns
- Maximum shot length: 1us
- Pulse repetition frequency: 1 pulse - 100kHz (maximum pulse length decreases as frequency increases)
- Trigger signal: 3,3-5V (50 ohm connection)
- Current reading: 20A/V (50 ohm connection)
- Supply voltage: 12V-0,2A / 24V-0,1A

ENVIRONMENTAL SPECIFICATIONS

- Operating temperature: -35° C / +50° C
- Storage temperature: -40° C / +70° C

GENERAL SPECIFICATIONS

- Pulse length control with trigger signal (15ns-1us)
- Up to 100kHz pulse repetition frequency
- Different input voltage options (12-24V)
- Current reading pin
- The laser diode can be soldered directly to the pads on the GEM-DLS40.
- Along with its small size, the GEM-DLS40 is designed for ease of use.
- It eliminates the need for multiple peripheral supply units.
- A single dc supply (12-24V) and trigger signal are sufficient for operation.

PHYSICAL SPECIFICATIONS

- Weight: 9g
- Size: 33mm x 49mm



www.gempanet.com.tr info@gempanet.com.tr +90 312 426 14 80

Dicle Caddesi, Akarçay Sk. No:3, 06800 Beysukent-Çankaya/ANKARA